



FOGGING DEVICE SPECIFICATIONS

ELECTRIC COLD-FOG ULV/MIST SPRAYER

The body and tank of the ULV Mist Sprayers are made from high-density chemical resistant polyethylene.

The applicator is used for dispensing most chemicals which are labelled for aerosol or mist applications such as disinfectants, deodorizers, germicides, insecticides, etc.

The particle sizes generated range from 7 – 30 microns in diameter.



ELECTRIC MOTOR:

- Continuous duty
- 220V AC
- 3.4 AMPS
- 50/60 Hz
- 20 000 RPM
- 1000W Power

DEVICE DIMENSIONS AND OUTPUT:

- Length – 28.58cm
- Width – 26.04cm
- Height – 41.28cm
- Tank capacity – 4L
- Output – 0-19 L/H
- Droplet throw – 15M



FLOW RATE:

Turning the knob of the metering valve regulates the flow rate. If the knob is rotated clockwise, the flow rate will be reduced. If the knob is rotated counter clockwise, the flow rate will be increased.

METERING VALVE SETTING	FLOW RATE AND DROPLET SIZE		
	FLOW RATE		DROPLET SIZE
	ML/MIN	L/H	MICRONS/VMD
LOW	70	4.2	14
MED	225	13.2	20
MAX	330	19.8	25



CONTACT DETAILS

IQ Green Solutions (Pty) Ltd

Unit 12, Urban Growth Park

15 Jan van Riebeeck Drive

Paarl, Western Cape

South Africa

Phone: +27(0)21 3000 530

www.iq-greensolutions.com

info@iq-greensolutions.com

